

Learning with Noisy Supervision

<https://wsl-workshop.github.io/ijcai21-tutorial>

Masashi Sugiyama (RIKEN/U Tokyo)

Tongliang Liu (U Sydney)

Bo Han (Hong Kong Baptist U)

Quanming Yao (Tsinghua U)

Gang Niu (RIKEN)



Schedule at a Glance

2

UTC-4 (Montreal)

20:00-20:15	Overview of Learning with Noisy Supervision Masashi Sugiyama (RIKEN/U Tokyo)
20:15-21:10	Statistical Learning with Noisy Supervision Tongliang Liu (U Sydney)
21:15-22:10	Deep Learning with Noisy Supervision Bo Han (Hong Kong Baptist U)
22:15-23:10	Automated Learning from Noisy Supervision Quanming Yao (Tsinghua U)
23:15-24:10	Beyond Class-Conditional Noise Gang Niu (RIKEN)



Overview of Learning with Noisy Supervision

Masashi Sugiyama

RIKEN Center for Advanced Intelligence Project/
The University of Tokyo



<http://www.ms.k.u-tokyo.ac.jp/sugi/>




東京大学
THE UNIVERSITY OF TOKYO



Ordinary Classification

- (Clean) training data: $\{(\mathbf{x}_i, y_i)\}_{i=1}^n \stackrel{\text{i.i.d.}}{\sim} p(\mathbf{x}, y)$



$\mathbf{x} \in \mathbb{R}^d$: Input pattern

$y \in \{1, \dots, c\}$: Clean class label

$p(\mathbf{x}, y)$: Clean data density

- Training error minimization: $\min_{\mathbf{g}} \hat{R}(\mathbf{g})$

$$\hat{R}(\mathbf{g}) = \frac{1}{n} \sum_{i=1}^n \ell(y_i, \mathbf{g}(\mathbf{x}_i))$$

$\mathbf{g}(\mathbf{x}) \in \mathbb{R}^c$: Classifier

$\ell(y, \mathbf{g}(\mathbf{x})) \in \mathbb{R}$: Loss

- Statistically consistent and work well.


$$\operatorname{argmin}_{\mathbf{g}} \hat{R}(\mathbf{g}) \xrightarrow{n \rightarrow \infty} \operatorname{argmin}_{\mathbf{g}} R(\mathbf{g})$$

$$R(\mathbf{g}) = \mathbb{E}_{p(\mathbf{x}, y)} \left[\ell(y, \mathbf{g}(\mathbf{x})) \right]$$

Classification with Noisy Supervision 5

Noisy training data:

$$\{(\mathbf{x}_i, \tilde{y}_i)\}_{i=1}^n \stackrel{\text{i.i.d.}}{\sim} \tilde{p}(\mathbf{x}, \tilde{y})$$



$\tilde{y} \in \{1, \dots, c\}$: Noisy class label

$\tilde{p}(\mathbf{x}, \tilde{y})$: Noisy data density

Training error minimization: $\min_{\mathbf{g}} \tilde{R}(\mathbf{g})$

$$\tilde{R}(\mathbf{g}) = \frac{1}{n} \sum_{i=1}^n \ell(\tilde{y}_i, \mathbf{g}(\mathbf{x}_i))$$

$$\operatorname{argmin}_{\mathbf{g}} \tilde{R}(\mathbf{g}) \stackrel{n \rightarrow \infty}{\not\rightarrow} \operatorname{argmin}_{\mathbf{g}} R(\mathbf{g})$$

- No longer consistent and does not work well.

How can we handle noisy data?

Generic Approach (1)

6


■ Unsupervised noisy data removal:

- Hotelling's T^2 statistics,
- k-means clustering,
- local outlier factor (LOF).

Breunig et al. (SIGMOD2000)



https://en.wikipedia.org/wiki/Harold_Hotelling




https://en.wikipedia.org/wiki/Local_outlier_factor

- ## ■ Easy to use, but this is completely heuristic and **no supervision is used.**



Generic Approach (2)

7

- **Regularization**: keeping the norm of the model parameters small for preventing overfitting.
 - Tikhonov regularization



https://en.wikipedia.org/wiki/Andrey_Nikolayevich_Tikhonov



<https://en.wikipedia.org/wiki/Overfitting>


- Nice theory, but smoothing is not enough to cope with strong label noise.

Generic Approach (3)



8

■ **Robust statistics**: suppressing the influence of noisy data by a gentle loss

- Huber loss,
- Ramp loss.



https://en.wikipedia.org/wiki/Peter_J._Huber



■ Nice theory for regression (additive noise), but **not very robust in classification (flipping noise)**.

Aim of This Tutorial

9

- The generic approaches were NOT specially designed for handling label noise.
- In this tutorial, we introduce recent advances in **multi-class classification that explicitly handle noisy supervision:**
 - Explicit modeling of label noise and systematic elimination of its influence.
 - Selecting clean samples/correcting noisy labels for robust deep learning.
 - Various industrial applications.
 - Advanced topics beyond class-conditional noise.

Reference for This Tutorial

10

- Bo Han, Quanming Yao, Tongliang Liu, Gang Niu, Ivor W. Tsang, James T. Kwok, and Masashi Sugiyama:

A Survey of Label-noise Representation Learning: Past, Present and Future.

<https://arxiv.org/pdf/2011.04406.pdf>

Related Workshop Tomorrow


11

- We organize **IJCAI2021 Weakly Supervised Representation Learning Workshop:**

<https://wsl-workshop.github.io/ijcai21.html>

- Invited speakers:

- Sharon Li (U Wisconsin-Madison)
- Paroma Varma (Snorkel AI)
- Yu-Feng Li (Nanjing U)
- Alex Ratner (U Washington)
- Chang Xu (U Sydney)
- Yang Liu (UC Santa Cruz)
- Chunyuan Li (Microsoft Research, Redmond)



Schedule at a Glance

12

UTC-4 (Montreal)

20:00-20:15	Overview of Learning with Noisy Supervision Masashi Sugiyama (RIKEN/U Tokyo)
20:15-21:10	Statistical Learning with Noisy Supervision Tongliang Liu (U Sydney)
21:15-22:10	Deep Learning with Noisy Supervision Bo Han (Hong Kong Baptist U)
22:15-23:10	Automated Learning from Noisy Supervision Quanming Yao (Tsinghua U)
23:15-24:10	Beyond Class-Conditional Noise Gang Niu (RIKEN)

Enjoy the tutorial!